

Original post set 1820 by Hendricks with witnesses: 12" white oak S 7 links; 10" ash N 54 E 5 links per Marion County Atlas p. 14. Hasbrook 3-20-1860 called no stone but witnesses: 30" white oak N 4 W 33-1/2 links, 30" oak N 42-1/2 W 45 links per Warren Twp. Legal Survey Book p. 27. Voorhis 4-1864 called no stone but same witnesses per Warren Twp. Legal Survey Book p. 49. Monroe 1-13-1953 called road nail w/brass washer. Baden 8-5-55 called the same. Hankins 6-23-58 called the same. McLand 1-31-69 called the same. Howe 12-17-74 called RR spike. Wilcoxen 1-9-75 called same. Gries 8-20-87 called the same. Wilcoxen 9-19-94 called RR spike with punch mark. Excavated 3-28-98 by Wilcoxen and one RR spike was found 3" down, another RR spike fd 8" down over a stone 13" down. Harrison set. Retied 7-19-1999. Retied 4-2-2004 by Wilcoxen. Retied 7-28-09 by Wilcoxen.

REF.	DISTANCE	DESCRIPTION
1.	99.73'	NW corner of brick column
2.	73.38'	Mag nail w/MCSO washer S PwP no # 2" up
3.	45.46'	Top nut of fire hydrant
4.	101.38'	Mag nail SE PwP #58-551 24" up
5.	32.80'	PK nail NE PwP #59-551 4" up